



ComFi M9

4G LTE MIFI

产品规格书



Model	ComFi M9				
CPU	ZTE ZX297520V3				
Hardware Specs	Cellular	Band (Conditional Selective)	FDD	B1, B2, B3, B4, B5, B7, B8, B20, B28A, B28B, B66	
			TDD	B34, B38, B39, B40, B41	
			WCDMA	B1, B2, B4, B5, B8	
			GSM	850/900/1800/1900MHz	
		3GPP	FDD	3GPP R9 Cat.4	
			TDD	3GPP R9 Cat.4	
			WCDMA	3GPP R7&R8 HSDPA Cat.24(64QAM) HSUPA Cat.7(16QAM)	
		Transfer rate	FDD	up to 150Mbps DL, 50Mbps UL	
			TDD	up to 150Mbps DL, 50Mbps UL	
			WCDMA	Up to 21Mbps DL, 5.76Mbps UL	
		Cellular Antenna		2 x Built-in 4G Antenna	
		WiFi	IEEE 802.11b/g/n		
	WiFi Transfer Rate	Up to 300Mbps			
	WiFi Encryption	WPA / WPA2			
	WiFi Type	2.4GHz			
WiFi Antenna	2 x Built-in WIFI Antenna, 2 x 2 MIMO				
Battery	Li-ion 2100mAh				
Standby Time	up to 40 hours				
Working Time	Up to 5 hours				
Interface	Micro USB	1A Charging Input, RNDIS Cable			
	SIM	Standard 6 PIN SIM card slot			

		3V SIM Card and 1.8V SIM Card
	SD Storage	Micro SD card slot, up to 32GB capacity, SD 2.0 Class.6
	Button	Power (Pressing 3s to Power On, about 45s get ready for internet)
	Reset	Reset Button Hole (Pressing 5s to Return to Factory Settings)
Internet	WIFI	WIFI AP, Max 10 Client Support
	WIFI SSID	MiFi_XXXXXX
	Default WIFI PWD	12345678
Environment	Operating Temp.	-10°C to 60°C
	Operation System	Windows XP, Windows Vista, Windows 7, Windows 10 or later MAC OS X or later IOS 5 or later Android 2.4 or later
Software Platform	System	Android 6.0
Web Interface	Support Browser	Internet Explorer 8.0, Mozilla Firefox 40.0, Google Chrome 40.4, Safari version and above
	IP	http://192.168.0.1
	Login	Default Password: admin Language Select: Mandarin or English
	Status	Network Status, Info (APN, IP, Signal, Battery, Online Duration, WiFi Client)
	Network	APN Config: International Roaming On/Off, APN, Username, Password, Authorization type modification: Add New APN, Restore Default APN parameters.
		Network Traffic Statistics: Flow Rate Limit: After accumulated flow reaches the set value, the speed limit is set according to the set rate
	WIFI	WLAN Config: Change SSID, Encryption method, Max client connection, Support PBC-WPS;
	Management	Login Management: Change username and password
System Management: Device Restart, Shutdown, Restore Factory Settings		
System Information: View Software version, WLAN MAC address, IMEI Date time zone setting		

		Update Management: Network Time or GPS Time, default network time zone, automatic update time zone, custom time zone
		Phonebook Management: Add, Modify, Find, Delete contacts
	SMS Management	SMS Read, Delete, Send
	Micro SD	Web Sharing
Others	Dimension	60.8 x 94 x 17mm
	Weight	Approx. 80g
	Color	White or Black, Color can be customized for OEM

想要了解更多深圳星恒讯科技的产品

请浏览我们的官网: www.movingcomm.com

阿里巴巴店铺: <https://movingcomm.1688.com/>

注意

您购买的产品、服务或特性等应受星恒讯公司商业合同和条款的约束, 本文档中描述的全部或部分产品、服务或特性可能不在您的购买或使用范围之内。除非合同另有约定, 本公司对本文档内容不做任何明示或默示的声明或保证。

由于产品版本升级或其他原因, 本文档内容会不定期进行更新。除非另有约定, 本文档仅作为使用指导, 本文档中的所有陈述、信息和建议不构成任何明示或暗示的担保。

提供的信息可随时更改而不事先通知。深圳星恒讯科技可以随时在不发通知的情况下修改产品生命周期、规格和产品说明。以上信息是按“原样”提供, 深圳星恒讯科技对该信息的准确性、产品的特性、可用性、功能或列出产品的兼容性不做任何形式的声明或担保。请联系我们, 了解关于上述特定产品或系统的更多信息。

Copyright © 2017 Shenzhen MovingComm Technology. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

地址: 深圳市宝安区石岩街道水田社区长城路同富康
水田工业区5号楼4楼 邮编: 518108

电话: 86-755-23125215

传真: 86-755-23125215-802

邮箱: marketing@movingcomm.com

