

ComFi EL620

1200AC Wall Mounted Access Point

Product Specifications



- 1167Mbps Wireless Transfer Speed with Dual Band 2.4GHz and 5GHz Wi-Fi Frequency
- Wi-Fi On/Off Switch and Led Indicator For Easy to Use
- Seamless Roaming Between APs
- Standard 48V PoE Power Input (via WAN Port)
- For Universal Type-86 Wall Socket
- Support FIT/FAT Mode, Can Be Managed and Maintained By ACs

Product Description

The ComFi EL620 is a business-grade wall-mounted wireless access point with high building quality and ivory white casing appearance. It brings a high speed dual band Wi-Fi access experience with 2.4GHz IEEE 802.11b/g/n and 5GHz IEEE 802.11ac wireless technology for users. It also has a network port (RJ45 port) for wired connected application needs like IPTV, Top box, computer, smart device, and others. The ComFi EL620 can switch between FIT/FAT mode and support remote managed and maintained by ACs. It provides business functions like auto-channel and power adjustment that can automatically detect available channels of radios and select the channel with the least interference. Also, smart seamless roaming while the user is moving around in a building in between two or more AP. The ComFi EL620 is suitable to apply in hotels, dormitories, lobbies, lounges, shopping outlets, classrooms, serviced offices, etc.

Hardware Specifications

Model	ComFi EL620				
CPU	MT7628DAN + MT7613BEN				
Flash	8MB				
DDR2	64MB				
2.4GHz Wi-Fi Frequency	2.412 ~ 2.484GHz				
5GHz Wi-Fi Frequency	5.150GHz~5.850GHz				
2.4GHz Wi-Fi Standard	802.11b/g/n MIMO 2T2R				
5GHz Wi-Fi Standard	802.11a/n/ac				
2.4GHz Wi-Fi Antenna	2dBi Internal Antenna x 2				
5GHz Wi-Fi Antenna	2dBi Internal Antenna x 2				
SSID Hide	Support				
Data Rate	2.4GHz: 300Mbps 5GHz: 867Mbps				
Modulation	OFDM = BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM DSSS = DBPSK, DQPSK, CCK				
Max Users	64+				
2.4GHz Transmit Power	802.11b	11M	17 ± 2dBm	1M	19 ± 2dBm
	802.11g	54M	16 ± 2dBm	6M	18 ± 2dBm
	802.11n HT20	MCS7	15 ± 2dBm	MCS0	17 ± 2dBm

	802.11n HT40	MCS7	14 ± 2dBm	MCS0	16 ± 2dBm
5GHz Transmit Power	802.11a	54M	16 ± 2dBm	6M	18 ± 2dBm
	802.11n HT20	MCS7	15 ± 2dBm	MCS0	17 ± 2dBm
	802.11n HT40	MCS7	14 ± 2dBm	MCS0	16 ± 2dBm
	802.11ac HT80	MCS9	13 ± 2dBm	MCS0	15 ± 2dBm
2.4GHz Reception Sensitivity	802.11b	11M	-82dBm	1M	-94dBm
	802.11g	54M	-72dBm	6M	-90dBm
	802.11n HT20	MCS7	-70dBm	MCS0	-88dBm
	802.11n HT40	MCS7	-68dBm	MCS0	-86dBm
5GHz Reception Sensitivity	802.11a	54M	-72dBm	6M	-90dBm
	802.11n HT20	MCS7	-70dBm	MCS0	-88dBm
	802.11n HT40	MCS7	-68dBm	MCS0	-86dBm
	802.11ac HT80	MCS9	-58dBm	MCS0	-82dBm
Wireless Functions	Auto-Channel Selection				
	Distance Control (802.1x Ack Timeout)				
	Multiple SSID (4 SSID)				
	BSSID				
2.4GHz Wireless EVM	802.11b: ≤-10dB 802.11g: ≤-25dB 802.11n: ≤-28dB				
5GHz Wireless EVM	802.11a: ≤-25dB 802.11n: ≤-28dB 802.11ac: ≤-32dB				
PPM	±20ppm				
Operation Mode	AP Mode, Gateway Mode, Repeater Mode				
Wi-Fi Encryption	Open, WPA, WPA2, WPA-PSK, WPA2-PSK				
WAN	1 x 10/100Mbps WAN Port Auto MDI/X Support IEEE 802.3af 48V PoE				
LAN	1 x 10/100Mbps LAN Port Auto MDI/X				
Reset	1 x Reset Pin-hole (Short press 1 time: Light Off, Short press 2 time: Light off and Wi-Fi off, Long press 10 second to perform factory reset)				
PoE	48V (IEEE 802.3af), 0.5A				
LED Indicators	SYS indicator				

Power Consumption	< 8W
ESD-I	Air Discharge: $\pm 4\text{KV}$
Surge	Common Mode: $\pm 2\text{KV}$
Size	86 x 86 x 35MM
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, Windows 8, Windows 10, MAC OS, NetWare, UNIX or Linux
Working Environment	Working Temperature: -20°C to 55°C Max Working Temperature: -30°C to 55°C Storage Temperature: -40°C to 70°C Humidity: 5% ~ 95% (Non condensing)
AC Control Management	Optional: support AP management via AC controller (under FIT AP mode)

Product Views



Order Information

Model	WiFi ON/OFF Switch	LAN Ethernet Port	FIT/FAT Mode*
ComFi EL620	✓	✓	✓
Standard Product Packaging <ul style="list-style-type: none"> • 1 x ComFi EL620 Wall Access Point Device • 2 x Installation Screws • 1 x User Manual • 1 x Warranty Card 			

*FIT AP mode is maintained and managed by ACs.

To see more MovingComm products,

Visit:-

Movingcomm official website <http://www.movingcomm.com/en>

Movingcomm Alibaba global site: <https://movingcomm.en.alibaba.com>

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN MOVINGCOMM'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2022 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone,
ChangCheng Road, ShuiTian Community, ShiYan, BaoAn
District, 518108 ShenZhen, GuangDong, China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: sales@movingcomm.com

