



ComIn I5000

AX3000 Industrial Grade 5G Wi-Fi 6 Wireless Router

- **Gigabit Ethernet Ports**
- **Serial Port Transparent Transmission**
- **Support DC Wide Voltage Power Supply Optional**
- **3000Mbps Dual-band Wi-Fi 6**

Product Description

ComIn I5000 is an industrial-grade 5G router with dual-band Wi-Fi 6, suitable for outdoor areas that require wireless coverage, such as computer room monitoring, power monitoring, environmental monitoring, and outdoor areas. ComIn I5000 supports 2T2R 802.11ax, and the maximum concurrent connection rate of dual-band can reach 3000Mbps, which can build a stable and high-speed wireless network for users. ComIn I5000 has high-performance wireless indicators, can obtain a larger wireless coverage area and better wall penetration performance, and meets the application scenario requirements of high-density wireless terminals.

At the same time, ComIn I5000 also has good compatibility and supports the access of most wireless terminals on the market. Users can easily connect using mobile phones, tablets or laptops.

This product is suitable for different application scenarios, such as vehicle-mounted Wi-Fi, video transmission, PLC remote control, smart express cabinets, video surveillance, 5G coverage, etc.

Main Features

Wi-Fi 6 (802.11ax) Standard

- As the latest generation of IEEE 802.11 Wi-Fi standard, 802.11ax can improve user access capacity and bandwidth in high-density access scenarios, reduce service latency, and enhance user experience;
- Supports 2.4GHz and 5GHz dual-band UL / DL MU-MIMO, enabling AP to send data to multiple terminals at the same time, doubling the utilization of wireless spectrum resources;
- Supports 1024QAM modulation, and data transmission efficiency is increased by 40% compared to 802.11ac (256QAM);
- Support UL / DL OFDMA technology, using different subcarriers to transmit data to multiple terminals at the same time, reducing delay and improving network efficiency;
- Supports spatial multiplexing technology, and through the BSS coloring mechanism, APs and terminals can distinguish overlapping BSSs (basic service sets) to minimize co-channel interference;
- Supports the target wake time* mechanism, allowing the AP and terminals to negotiate sleep and wake time, reducing conflicts and unnecessary wake-up times between terminals, saving terminal power and improving battery life.

Uplink and Downlink Multi-user - Multiple Input Multiple Output (MU-MIMO)

Supports MU-MIMO technology, supporting up to 4 spatial streams, 2.4GHz band supports 2 spatial streams, and 5GHz band supports 2 spatial streams. Through DL / UL MU-MIMO technology, AP can send data to multiple terminals at the same time, and the utilization rate of wireless spectrum resources is doubled, which increases the number of access users and bandwidth, and improves the user experience in high-density access scenarios .

High-speed Access

It supports 160M bandwidth. The increase in bandwidth brings about an increase in available data subcarriers and expands the transmission channel. In addition, the use of 1024QAM modulation, MU-MIMO and other technologies makes the 5G single-band rate reach 2.4Gbps and the whole device rate reach 3Gbps.

5GHz Priority

The AP supports dual-band access of 2.4GHz and 5GHz at the same time. By controlling the terminal to access the 5GHz band first, dual-band terminal users in the 2.4GHz band are migrated to the 5GHz band, reducing the load and interference on the 2.4GHz band and improving the user experience.

Industrial Application Design

- Wide input voltage design: 9 ~ 36V
- Industrial-grade software and hardware watchdog design, trouble-free and reliable operation in power stations, transportation, and industrial control environments
- Industrial-grade EMC electromagnetic compatibility and radiation performance, passed GB / T17626.5-2008 Level 4 test standard
- Industrial grade components, operating temperature: -30 ~ 60°C
- Industrial housing, suitable for extreme environments
- Adopt fanless cooling technology to effectively reduce the failure rate of equipment
- Meet the requirements for trouble-free and reliable operation in vibration and impact environments

Stable and Reliable

- Adopt a complete anti-dropout mechanism to ensure that the data terminal is always online
- The whole machine passes the EMC test requirements
- Ethernet interface has built-in 1.5KV electromagnetic isolation protection, GB / T17626.5- 2008 level 4
- SIM / UIM interface has built-in 15KV ESD protection, GB / T17626.5-2008 level 4
- The power interface has built-in reverse phase protection and overvoltage protection

Mobile Network

- Support dual-channel 5G SA / NSA network
- Support lock Band, lock base station
- Support PIN code lock card
- Supports locked network mode
- Support dual-channel hot backup
- Support load balancing

Product Specifications

Product Model	I5000
Overall Dimensions	190*139*27mm
Weight	705 g
Installation	Ear-mounted or rail-mounted installation
Indicator Lights	1 x PWR 1 x SYS 1 x Wi-Fi1 1 x Wi-Fi2 1 x NET 3 x Signal
Interface	5 x 1GbE RJ45 (1WAN, 4LAN) 2 x male RF interface (Wi-Fi) 4 x female RF interface (mobile network) 1 x Drawer-type dual Nano SIM card holder(4FF) 1 x 5 PIN 3.5mm phoenix terminal (RS232 or RS485) 1 x 2 PIN 3.5mm phoenix terminal (DC Input) 1 x DC interface 1 x TF Card
Phoenix Terminal	Specifications: 5 x 3.5mm RX (RS232) TX (RS232) GND (RS232) B (RS485 B-) A (RS485 A+) Specifications: 2 x 3.5mm VIN (DC Input V+) GND(DC Input V-)
Input Voltage	9V~36V Recommended input 12V2A
Power Consumption	12W (full load)
Environmental indicators	
Ambient Temperature	Working temperature: -30°C ~ + 60 °C Storage temperature: -40°C ~ +85°C
Relative Humidity of Working Environment	5% ~ 95% (non-condensing)

Air Pressure	86kPa ~ 106kPa Altitude		
Certification	3C , other certifications can be completed according to customer requirements		
Main chip solution			
CPU	MTK MT7981BA+MT7976CN+MT7531AE		
Flash	32 MB SPI Flash		
DDR	256MB DDR3L memory		
Wi-Fi Features			
Working Frequency Band	2.4GHz radio:2.412GHz~2.472GHz		
	5GHz radio: 5.180~5.825 GHz		
Maximum Output Power	2.4GHz radio: 21± 2dBm@MCS0		
	5GHz radio: 21±2 dBm@MCS0		
Supported Rate	2.4G Radio: 802.11b: 1, 2, 5.5, and 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, and 54Mbps 802.11n HT20 / HT40: MCS0~MCS15 (400 / 800ns GI) 802.11ax HE20 / HE40: MCS0 ~ MCS11 (400 / 800ns GI)		
	5G Radio: 802.11a: 6, 9, 12, 18, 24, 36, 48 and 54Mb / s 802.11n HT20 / HT40: MCS0~MCS15 (400 / 800ns GI) 802.11ac VHT20 / VHT40 / VHT80: MCS0 ~ MCS9 (400 / 800ns GI) 802.11ax HT20 / HE40 / HE80 / HE160: MCS0 ~ MCS11 (400 / 800ns GI)		
Receiving Sensitivity	802.11g: -92dBm@6Mbps		
	-76dBm@54Mbps		
	802.11n:		
		HT20	HT40

	MCS0 / 8 / 16	- 89 dBm	- 87 dBm	
	MCS7 / 15	- 73 dBm	- 71 dBm	
802.11a: -92dBm@6Mbps -76dBm@54Mbps				
802.11ac:				
	VHT20	VHT40	VHT80	
	MCS0	- 90 dBm	-87dBm	-84dBm
	MCS8	- 70 dBm	-68 dBm	-59 dBm

5G Wireless Parameters

Wireless Access Technology	5G: 3GPP Release 15 NSA / SA operation, Sub-6 GHz CN LTE: Downlink Cat 12, Uplink Cat 13 GL&EU: Downlink Cat 19, Uplink Cat 18		
Frequency Band Support	CN(domestic)	EU	GL (Global)
	NSA: n41 / n78 / n79 SA: n1 / n28 / n41 / n77 / n78 / n79 MIMO DL 4 × 4 MIMO: n1 / 41 / 77 / 78 / 79 UL 2 × 2 MIMO : n41 / 77 / 78 / 79 DL 2 × 2 MIMO: n28 LTE Category : DL Cat 12, UL Cat 13 LTE-FDD: B1 / B2 / B3 / B5 / B7 / B8 / B20 / B28 LTE-TDD: B34 / B38 / B39 / B40 / B41 WCDMA: B1 / B2 / B5 / B8	NSA: n1 / n3 / n5 / n7 / n8 / n20 / n28 / n38 / n40 / n41 / n71 / n75 / n76 / n77 / n78 SA: n1 / n3 / n5 / n7 / n8 / n20 / n28 / n38 / n40 / n41 / n71 / n75 / n76 / n77 / n78 LTE-FDD: B1 / B3 / B5 / B7 / B8 / B20 / B28 / B32 / B71 LTE-TDD: B38 / B40 / B41 / B42 / B43 WCDMA: B1 / B5 / B8	5G NR (NSA): n1 / 2 / 3 / 5 / 7 / 8 / 12 / 13 / 14 / 18 / 20 / 25 / 26 / 28 / 29 / 30 / 38 / 40 / 41 / 48 / 66 / 70 / 71 / 75 / 76 / 77 / 78 / 79 5G NR (SA): n1 / 2 / 3 / 5 / 7 / 8 / 12 / 13 / 14 / 18 / 20 / 25 / 26 / 28 / 29 / 30 / 38 / 40 / 41 / 48 / 66 / 70 / 71 / 75 / 76 / 77 / 78 / 79 LTE-FDD: B1 / 2 / 3 / 4 / 5 / 7 / 8 / 12 / 13 / 14 / 17 / 18 / 19 / 20 / 25 / 26 / 28 / 29 / 30 / 32 / 66 / 71 LTE-TDD: B34 / 38 / 39 / 40 / 41 / 42 / 43 / 48 LAA: B46 WCDMA: B1 / 2 / 4 / 5 / 8 / 19

Uplink and Downlink Peak Rates	5G SA Sub-6: Max. 2Gbps(DL) / Max. 1Gbps(UL) 5G NSA Sub-6: Max. 2.2Gbps(DL) / Max. 575Mbps(UL) LTE: Max. 600Mbps (DL) / Max. 150Mbps (UL) WCDMA: Max. 42 Mbps (DL) / Max. 11 Mbps (UL)	5G SA Sub-6: Max. 2.4Gbps(DL) / Max. 900Mbps(UL) 5G NSA Sub-6: Max. 3.4Gbps(DL) / Max. 550Mbps(UL) LTE: Max. 1.6G bps (DL) / Max. 200Mbps (UL) WCDMA: Max. 42 Mbps (DL) / Max. 5.76 Mbps (UL)
Antenna Type	External antenna	
Antenna Gain	3Dbi	

Ordering Information

Product Model	Product Packaging
ComIn I5000	Product complete machine, 12V1.5A power adapter , 2.4&5.8 dual-band Wi-Fi antennas * 2 , 5G antennas * 4 , installation accessories, network cable

To see more MovingComm products,

Visit:-

Movingcomm official website <http://www.movingcomm.com/en/>
Movingcomm Alibaba global site: <https://movingcomm.en.alibaba.com>

The information provided in this document is related to Movingcomm products. This document does not grant any express or implied license of intellectual property rights through estoppel or other means.

Unless otherwise specified in the terms and conditions of Movingcomm's sale of such products, Movingcomm assumes no responsibility and does not assume any express or implied warranties related to the sale and / or use of Movingcomm products, including liability or warranties related to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property rights.

Unless otherwise agreed in writing by Movingcomm, the design or intent of Movingcomm's products is not applicable to any application scenario that may result in personal injury or death.

Movingcomm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from Movingcomm prior using the product. Movingcomm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2025 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone,
ChangCheng Road, ShuiTian Community, ShiYan, BaoAn
District, 518108 ShenZhen, GuangDong, China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: sales@movingcomm.com

