

## ComFi MG11

### Portable 4G WiFi6 MIFI

- New Design and Material
- Support Custom 4G LTE CAT4 LTE-FDD and LTE-TDD Bands
- Support WiFi6
- 10000mAh High Battery Capacity for Long Hours
- Support Global Operators ' SIM Cards



## Product Description

The ComFi MG11 is a simple-looking portable LTE wireless device, which offers convenient wireless broadband access with superior wireless access performance and comprehensive routing capabilities. It can transmit wireless local area network data through the high-speed LTE wide area network so that user devices like mobile phones, laptops, tablets, and other devices can access the Internet through the ComFi MG11 simultaneously



## Hardware Specifications

Main Chipset	ASR 1803
SIM	1.8V/3.0V Nano SIM Card Slot
USB	1 x USB Port Input 1 x Micro USB Port Output 1 x Type-C Port Output 1 x Lightning Port Output
Power Button	Long press 5 sec to ON/OFF the device
Reset	Long press 3 sec to perform factory setting reset
LED Indicator	Power, WiFi, 4G
Battery	Detachable, Battery Capacity 10000mAh
Working Time	Up to 5hours

Standby Time	Up to 40hours
Size	70mm (L) x 164mm (W) x 20mm (H)
Weight	Approx. 233g
Operating Temp.	-10°C to 45°C
Storage Temp.	-25°C to 60°C
Operating Humidity	10% ~ 95%RH, non-condensing

### 4G/3G Technical Specifications

3GPP/3GPP2 Standard	LTE FDD, LTE-TDD, Release 9, Cat4	
Frequency	China Version	FDD: B1, B3, B5, B8 TDD: B38, B40, B41 WCDMA: B1, B8
	Europe Version	FDD: B1, B3, B5, B7, B8, B20, B28 TDD: B38, B40, B41 WCDMA: B1, B5, B8
Data Rate	LTE-FDD: Max 150Mbps DL / Max 50Mbps UL	
	LTE-TDD: Max 150Mbps DL / Max 50Mbps UL	
	WCDMA: Max 21Mbps DL / Max 5.76Mbps UL	
Rx Sensitivity	Compliance with 3GPP Release 9 Standard	
MIMO	2T2R, DL MIMO 2x2	
Antenna Type	Internal Antenna	

### WIFI Specifications

Chip Solution	AIC8800DW
Protocol Standards	IEEE 802.11b/g/n/ax
Channel Bandwidth	20MHz, 40MHz
Frequency	2.4GHz
TX/RX	1T1R

Peak Rate	802.11b: 11Mbps 802.11g: 54Mbps 802.11n: 75/150 Mbps 802.11ax: 286Mbps/229Mbps
Receiving Sensitivity	<-76dBm at the antenna port,QPSK,11Mbps,1024 Byte PSDU @ 802.11b <-65dBm at the antenna port,64QAM,54Mbps,1024 Byte PSDU @ 802.11g -64dBm at the antenna port,64QAM,65Mbps,4096 Byte PSDU @ 802.11n(HT20) <-61dBm at the antenna port,64QAM,135Mbps,4096 Byte PSDU@ 802.11n(HT40)
Maximum Transmit Power	17 dBm @ 802.11b 15 dBm @ 802.11g 14 dBm @ 802.11n 12 dBm @ 802.11ax
Antenna Type	Internal antenna
Users	Max 16

## Software Functions

Language	Chinese, English	
OS	Android 6.0	
Browser Support	Internet Explorer 8.0, Mozilla Firefox 40.0, Google Chrome 40.4, Safari or above version	
IP Address	<a href="http://192.168.100.1">http://192.168.100.1</a>	
Login Access	Default user and password: admin	
Default WIFI SSID	4G-MFI-xxxxxx	
Default WIFI Password	1234567890	
Function	Network Info	Network Status, Info (APN, IP, Signal, Battery, Online Duration, WIFI Client)
	Network	APN Configuration: Roaming ON/OFF, APN, Username, Password
		Authorization type modification: add APN, restore default APN parameters

		Network traffic statistics: Flow limit: After the accumulated flow reaches the set value, set the speed limit according to the set flow
	WIFI	WLAN Configuration: Change SSID, Encryption Method, Max Client Connection, Support PBC-WPS
	Management	Login Management: Change Username and Password
		System management: device restart, shutdown, factory reset
		System information: View software version, WLAN MAC address, IMEI date and time zone settings
		Update management: network time or GPS time, default network time zone, automatic update time zone, custom time zone
		Phonebook management: add, modify, search, delete contacts
	SMS	SMS read, delete, send
	Micro SD	Network Sharing

### Order Information

Model	Casing Color	4G Band Combination
ComFi MG11	White	CN/EU Version*
	Black	CN/EU Version*

\* Sample product specs and cellular bands may vary from time to time. We support customers' requirements by custom bands for 4G service providers in a particular region or country. Terms and conditions applied.

To See More MovingComm Products,

Visit:-

Movingcomm official website <http://www.movingcomm.com/en/>

Movingcomm Alibaba global site: <https://movingcomm.en.alibaba.com>

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT.

EXCEPT AS PROVIDED IN MOVINGCOMM' S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2022 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

**深圳星恒讯科技有限公司**

**SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.**

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial  
Zone, ChangCheng Road, ShuiTian Community, Shi  
Yan, BaoAn District, 518108 ShenZhen, Guangdong,  
China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: [sales@movingcomm.com](mailto:sales@movingcomm.com)

