

ComIn SD2F8T-SFP-POE

Unmanaged 8-Port GbE PoE Switch with 2 SFP Port

Product Specifications



Product Description

The SD2F8T-SFP/SD2F8T-SFP-POE family model is an unmanaged 8-Port Gigabit and 2 x Gigabit SFP Optical port industrial-grade Ethernet switch. It features support for 8 x 10/100/1000Base-T adaptive RJ45 ports, with the optional POE feature available.

The SD2F8T-SFP/SD2F8T-SFP-POE family model products are designed with a focus on industrial standards, including materials and product design. The enclosure is crafted from aluminum alloy, ensuring superior heat dissipation for efficient performance. The fanless heat dissipation circuit design allows for a wide range of working temperatures, while also providing a high level of protection. These technologies contribute to the exceptional industrial-grade quality of the products, making them resistant to both high and low temperatures and offering protection against lightning and other potential hazards. Additionally, the products feature industrial-grade three-level ESD protection, making them suitable for various applications, such as intelligent transportation, outdoor monitoring, industrial networks, and deployments in smart cities and other challenging environments.


Product Specifications

INTERFACE	
Uplink Port Interfaces	2 x 1000Base-X SFP
Network Port Interfaces	8 x 10/100/1000Base-T
Power Connector	5P Phoenix Terminal, Dual Power Supply Redundancy
LED lights	Power indicator: PWR (Green); Optical: FX (Green) Network Port Indicator: Yellow (1000 or PoE) Green (Link)
CABLE TYPE AND DISTANCE	
Twisted pair	0-100m (CAT5e, CAT6)
Single-mode fiber	20/40/60/80/100/120KM
Multimode fiber	550m/2KM
Fiber interface	LC/SC
Network Topology Mode	
Star topology	Support
Bus topology	Support
Tree topology	Support
ELECTRICAL CHARACTERISTICS	

Input Voltage	DC10-55V/AC 100-240V 50-60HZ
Power Consumption	Non-PoE Total Power <10W, With PoE < 132W (Full Load)
POE SUPPORT (OPTIONAL POE FEATURE)	
PoE Port	1-8
PoE Protocol	802.3af, 802.3at
PoE Pinout	1,2,3,6
PoE Management Mode	Not Supported
LAYER 2 SWITCHING	
Swap Capacity	20G
Packet Forwarding Rate	14.9Mpps
MAC Address Table	16K
VLAN Support and Number	Supports 4096 VLAN ID
Report Buffer	1M
Forwarding Delay	<10us
Port Characteristics	Cross-Direct Adaptive
Flow Control	Support
Jumbo Frames	Support 10Kbytes
Storm Suppression	Support
PROTECTION	
IP Rating	IP40
Power Surge Protection	IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
Network Port Surge Protection	IEC 61000-4-5 Level 3 (6KV/2KV) (10/700us)
Radiated Immunity	IEC 61000-4-3 Level 3 (10V/m)
Instantaneous Pulse Immunity	IEC 61000-4-4 Level 3 (1V/2V)
Conduction Immunity	IEC 61000-4-6 Level 3 (10V/m)
Power Supply Frequency Magnetic Field Immunity	IEC 61000-4-8 Level 4 (30A/m)
Voltage Drop	IEC 61000-4-11 Level 3 (10V)
EMI	Class A
Electrostatic Discharge (ESD) Immunity	IEC61000-4-2 Level 4 (15KV/30KV)
Free Fall	0.5m

ENVIRONMENTAL CONDITIONS	
Operating Temperature	-40°C ~ +85°C
Storage/Transport Temperature	-40°C ~ +85°C
Relative Humidity	5%~95% (non-condensing)
Heat Dissipation Method	Fanless Enclosure Dissipates Heat
MTBF	100,000 Hours
MECHANICAL STRUCTURE	
Size	158 x 118 x 42mm
Installation Method	Rail Mounting
Housing Material	Industrial Aluminum Shell
Weight	0.75kg
RELEVANT CERTIFICATIONS	
Certification	CE, FCC, RoHS
PACKAGES AND ACCESSORIES	
Standard Packaging	Equipment, Terminal Block, Manual, Power Adapter (Optional)

Product Size and Dimension



Order Information

Order Code	Product Description
ComIn SD2F8T-SFP	Unmanaged 8-Port GbE, 2 SFP Port Switch
ComIn SD2F8T-SFP POE	Unmanaged 8-Port GbE, 2 SFP Port PoE Switch

To see more MovingComm products,

Visit:-

Movingcomm official website <http://www.movingcomm.com/en>

Movingcomm Alibaba global site: <https://movingcomm.en.alibaba.com>

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN MOVINGCOMM'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2023 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone,
ChangCheng Road, ShuiTian Community, ShiYan, BaoAn
District, 518108 ShenZhen, GuangDong, China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: sales@movingcomm.com

